25X1 Approved For Release 2009/09/21 : CIA-RDP80-00810A004301100009-3 CLASSIFICATION SECRET CENTRAL INTELLIGENCE AGENCY REPORT INFORMATION REPORT CD NO. 20 June 1954 DATE DISTR. COUNTRY East Germany 25X1 **SUBJECT** NO. OF PAGES Development of an Adcock Direction Finder at VEB Funkwerk Koepenick NO. OF ENCLS. PLACE 25X1 (LISTED BELOW) **ACQUIRED** SUPPLEMENT TO DATE OF INFO. REPORT NO. THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES, WITHIN THE MEANING OF TITLE 18, SECTIONS 793 AND 794, OF THE U. S. CODE. AS AMENDED. ITS TRANSMISSION OR REVELATION OF ITS CONTENTS TO OR RECEIPT BY AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW THE REPRODUCTION OF THIS FORM IS PROHIBITED. 25X1 THIS IS UNEVALUATED INFORMATION direction Development of an Adcock direction finder in Department TEE of Funkwer 25X1 Koepenick which was resumed in late March 1954 1/ was placed under the direction of Ing. Hans Erler. After Erler defected to the West in April 1954, the development was placed under the supervision of Ing. Schneider (fnu). 2. Selection of the personnel for the development project met with many difficulties. In mid-May 1954 the following persons were charged with the development of individual stages of the instrument: Fritz Koehler, Jens-Peter Rehahn, and Gisela Pilat are developing the six wide band masts of the instrument. Benke (fnu) and Wolfgang Meinke are developing the receiver. Guenther Raskin is developing the input stage with the goniometer. Funds allowed for the development in 1954 amounted to 260,000 DME. No date has yet been set for the completion of the project. The following are technical specifications of the instrument: dipertion The instrument is to be a mobile six-mast Adcock direction finding installation with vertical polarized antennae. b. Frequency range: 4 to 30 mcs.

•

Direction

degree minimum width.

25X1

4

25 YEAR RE-REVIEW

	CLASSIFICATION	SECRET		
STATE	#x NAVY → NSRB	DISTRIBUTION	ORR EV X OST EV X	
ARMY	Approved For Release	9 2009/09/21 : CIA-RDP80	)-00810A004301100009-3 <sup>-</sup>	

c. Direction finding sensitivity: less than 20 micro-V/m at one